

## 1/2 Ton Bonestock Truck

Any 80s and newer 1/2 ton trucks

### **Drivetrain**

1. No cross-breeding motors/transmissions, must be factory bolt in.  
No modifications
2. Drivetrain must be OEM spec (motor, transmission and rear end)
3. Only after market parts allowed are headers and shifter
4. 4x4 must be disconnected
5. Must have stock driveshaft
6. DOT tires only
7. Fuel tank/cell must be relocated to safe position

### **Cage**

1. May have a simple floating 4 point cage
2. Highly recommend halo and has to be attached to sheet metal only, **cannot go to frame**

### **Body/Frame**

1. Hood must have a 12"x12" hole
2. Hood and tail gate can be tied down in 4 places using 3/8 chain or 3 loops of 9wire
3. Doors may be chained or wired shut in 4 spots and drivers door can be welded shut
4. Bumpers can be changed to 4x4" 1/4" thick flat tube **NO POINTS.**  
Or you can have any 80s and newer flat car bumper. You cannot

shorten frame and cannot have bumper brackets. Bumpers can be welded on

5. Must have stock body mounts. If a body/box mount is rusted out you may use 1 loop of 3/8 chain or 3 strands of 9wire
6. May have a total of (4) 3/8" bolts bolted from cab to box

**IF IT IS NOT STATED IN THE RULES, YOU CANNOT DO IT**

**Questions: call/text**

**Hunter**

**507-993-6337**