

General Rules

1. All drivers must sign in and register.
2. All rules will be enforced; follow them or you will participate.
3. Any driver or pit crew member disobeying the rules, or acting in unsportsmanlike conduct will be disqualified or banned from future derbies.
4. All drivers are to obey the track officials at all times.
5. No pit crew members or spectators are allowed on the track at any time.
6. Any driver or pit crew member consuming or under the influence of drugs and/or alcohol will be moved.
7. If your car does not pass inspection and the driver is unwilling to make the changes in three (3) attempts; you will be disqualified.
8. All drivers must attend a mandatory drivers meeting. Any controversies or concerns should be addressed at the drivers meeting in a civil manner.
9. Any decisions made by an official are final.

Driver Safety

1. Competition appeal must consist of a heavy long sleeved jacket and long pants or fire suit, D.O.T. or full face helmet, eye protection, and closed toed shoes; such as tennis shoes or boots. Failure to wear such gear will get you disqualified from the show/event.
2. Also you must wear your seat belt in competition at all times; this is mandatory if this is rule is provoked you will be disqualified. However, if any of these items above come loose or come off; the competition will be paused. If the driver is unable to place the item back into position, they will be disqualified.
3. **NO DRINKING ALLOWED!**

Stock V8 Large Car Rules

Brooksville Pulling Association

Semi Stock Class Rules

- Roof signs, car numbers must be 22" tall minimum. They must be located clearly on roof and both sides of car on doors.
- Class includes; any FWD car, station wagon or FWD minivan.
- NO RWD mini vans, 4x4, imperials, Hearse, checker cabs, SUV or mini trucks.

Semi Stock Class Preparation:

- Car must be stripped of all plastic and glass, as well as carpet and debris and fabric. Nothing flammable nor anything that had the potential to break free may stay in the car. Car must be vacuumed out and free of all debris.
- Note: Computer electrical ECU cars may keep dash, but at OWN RISK.
- NO WELDING ON CAR UNLESS IT'S STATED!

Drivetrain:

- Motor and transmission swap is ok. Must be mounted with stock motor mounts in stock location.
 - No braces or protectors whatsoever.
 - Rear drive axle cars must be a "Passenger car rear axle"
 - You can weld spider gears to make it POSI, but that is it.
 - No slider driveshafts
 - Aftermarket shifter is ok
 - Aftermarket gas pedal is ok
 - Headers are ok
-
- All suspension must have free movement front and rear, may chain rear humps with max 3/8 chain but must have slack, no welding links. Leaf spring cars can have no more than 7 leafs per side, no more than 3 clamps per Leaf pack, per side.
-
- Front bumper may be changed with any stock passenger car bumper and welded to frame with a 4"x4" x 3/16" angle or 4"x4" x 3/16" plate (one or the other, cannot use both), only two pieces of plate or angle per frame rail, or factory car bumper brackets that came with make, model of that car entered. (you cannot use combination of bumper mounting methods, "only one method of the three" described) use to mount front bumper of car only.

Body Bolts may be changed to max of 5/8 " all thread, nut and washer must remain inside of frame and stock body pucks must remain in place as from the factory as well with the exception of the front 2 radiator support bolts may go through the radiator support and will count as 2 of the 4 hood bolts which if done so ONLY these 2 May be the 5/8" all thread / body bolt period!!!!

Frame: Frame stubs may be changed but must remain Chevy on Chevy, Ford on Ford, Mopar on Mopar (no imperial stubs). However, if you do so it can only be butt fitted to the existing frame and a single

Stock V8 Large Car Rules Brooksville Pulling Association

pass of weld all the way around as from the factory will be allowed, NO Extra plate can be added, PERIOD!!!!!!

No welding on frame other than specified in these rules will be Allowed. Frame may be tilted but if done so only welding allowed is where u cut the tabs to tilt it, you may weld it solid with a single pass only, no adding plate to do this.

All doors can be welded-exterior only (if welding, see weld restrictions***6point of 6"), 9 wire or chained.

Hood- can secure one of the 2 ways described:

- 4 points of 9 wire or 4 points of chain
- Maximum of 4 hood bolts are allowed, 2 x ½ all thread in the center of the hood, 2 front radiator support bolts may be the 5/8 all thread and go through hood to hold hood down and will count as 2 hood bolts as well, only these 2!!!!
- Hoods must be off or completely/fully open at time of inspection, only after inspection may you secure with the options described in hood section of rules.
- Hood must have 24" minimum hole in center for fire access

Windshield bar- Allowed one or two bars of rebar or 9 wire or chain or cable for driver protection. It can be attached to sheet metal only. Can be welded or bolted. 4" within the top bottom of windshield area and not make contact with any other components

****Mandatory driver's door bar protection!**

- Drivers door can be completely welded solid and may have a plate on it inside or outside for protection (driver side door bar cannot go past driver door seams of 8" maximum)

**** All other doors can only have 6 points of max 6"x2" ½"x 3/16" strap welded to secure them. Trunks may have maximum of (6), 6"Lx 2"W ½"x 3/16" plate welded. If welding seams 6" you cannot use 9 wire or chain applications. Same 6 point max applies if you 9 wire or chain ** only one option of the three (weld or chain or 9 wire) is available to use.**

****Mandatory- minimum 4 pt welded cage, 1 bar behind seat 1 bar from seat bar FWD on both sides. Max 10"x10" end plates are allowed.**

Safety will be strictly enforced! Small tack welds will not be allowed to compete. This is not a safe practice on cages.

Recommended 4 point cage system

Stock V8 Large Car Rules Brooksville Pulling Association

Any DOT STAMPED TIRE ONLY!!!!!!

You may cut firewall for distributor clearance but hole cannot be more than width of Intake manifold.

Must have functional seat belt.

You may prebend back of car to make it bend up, you may tuck trunk lid or v crease it across into the middle.

If gas tank is behind rear axle, it must be moved to inside the car and mounted properly NO more than 5 gallons of fuel, no plastic gas cans, can be used as fuel tanks. Battery may be mounted in car and must be fully secured, absolutely NO exceptions.

You may put a rollover halo bar in 5" maximum material, 2 bars must be vertical (no angled or tipped). Attached to sheet metal on floor only and back seat bar of cage. One bar across roof sheet metal, tying it to the vertical halo bars. Corners may use gussets, and top cross bar may be mounted to the roof at 2 points- consisting of maximum 6" of weld to roof sheet metal only. Absolutely no connecting to frame by any means, or come in contact with frame. Absolutely no added metal allowed. This is and will be a semi stock format and inspections will be enforced to the rules.

** These rule are to inform you as to what you can do to your cars for this class.**

Any questions; contact (352) 585-9775 for Richard Klimas

FWD Bone-Stock Small Car

Brooksville Pulling Association

1. FWD Rules

- 80's or newer car, NO mini van or station wagon.
- Maximum wheel base allowed is 110.5 inches.
- No leaf springs allowed.
- No RWD cars allowed.
- Preparation-ALL glass, plastic, lights, chrome, trailer hitches and body trim must be removed.
- ALL cars must be empty ceiling to floor boards. Headliner MUST be removed. Cars MUST be swept/vacuumed cleaned of any and ALL debris. ONLY fuel injected cars can retain factory dash for electrical purposes.
- ALL cars must have a race number at least 24 inches tall on both driver and passenger doors and on roof or a roof sign.
- Engines: ANY 3cyl, 4cyl, or 6cyl engine is allowed.
- NO V-8 Engines allowed.
- HEADERS are allowed.
- No pre-bending allowed.

2. FRAMES

- NO modifications to the frame can be made.
- NO hump plates
- FWD Continued

3. DRIVER DOOR

- MUST be painted white.
- Drivers door bar or plate is a MANDATORY requirement.
- ALL cars MUST have drivers door protection bar/plate inside or outside the car (protection bar is to be NO taller than 12 inches. Must be centered in or on the door) MUST be welded or bolted in. Driver side door ONLY. Door bar CANNOT extend further than 8 inches forward of the front door seam. Drivers door bar CANNOT extend beyond 8 inches of drivers door seam (must be mounted in a secure manner to ensure it protects the driver and WILL NOT come off). NOT to be used an effort to strengthen the car.

4. BUMPERS

- NO welding bumpers.
- NO changing bumpers

5. WINDSHIELD BAR or SCREEN REQUIRED

6. BATTERIES & FUEL

- ALL batteries and gas tanks MUST be secured and covered properly. FWD cars with factory fuel tank located in front of rear axle are permitted to leave fuel tank in factory location.

FWD Bone-Stock Small Car

Brooksville Pulling Association

- Battery & fuel cells may be relocated inside car. No ratchet straps, rope or wire will be permitted to secure fuel tanks or batteries for safety reasons. Battery box and fuel cells must securely be bolted and completely secured. Recommended a secured metal fuel cell of motorsports or marine application, absolutely NO plastic fuel cans permitted.

7. TRUNK, HOOD, and DOORS

- Can be tied we seatbelts, chain, or 9-wire.
- Must have a 5"x5" hole in the hood.

8. TIRES

- D.O.T. tires only.

9. SWAYBAR

- May NOT be modified in any way.

10. PROTECTORS

- NO protectors of any kind, NO engine or pulley protection allowed.

11. SUSPENSION

- ALL suspension MUST be stock for year, make and model of said car.

If not stated in the rules do not do it. The rules are to inform you as what will be allowed. If it was not mentioned in the rules, it will not be allowed. This class is to have a great low cost opportunity. Officials' decision is final!