2022 Hornet 4 Cylinder Demolition Derby Rules

Sunday July 3rd, 5:00pm (Chain & Go) 1st - \$2000, 2nd \$1000, & 3rd \$500

No full-size cars with 4 cylinder engines.

Dash must remain in vehicle, or a spread bar is required.

(1) One upright bar from the floor to roof must be as close to driver as possible to protect in case of rollover.

A maximum of <u>12"</u> steel plate must be bolted to the driver's side of vehicle minimum of <u>6"</u> from each wheel well. Passenger side is optional. <u>2</u> grader blades in place of steel plate acceptable.

All glass and burnable material must be removed. Seats remains.

Battery must be moved inside of vehicle.

Minimum of 3 point seatbelt harness must be used.

Windshields may remain (I suggest they be removed). **2** bars must be put in the windshield area to protect driver from large debris.

Doors, hood, trunk, hatch must be chained (not welded). Maximum of $\underline{\mathbf{4}}$ chains on hood and $\underline{\mathbf{2}}$ on doors and trunk/hatch.

Stock bumpers front & back (no reinforcing).

Disengage airbags.

No mirrors.

Fuel tank must be relocated to inside of vehicle or use fuel cell or metal tank. Metal boat tank acceptable with external fuel pump. – See addendum

Must sign waiver and release form date of race.

Social Security Number required for any payout over \$200.00

Questions? Contact Jeff Gruenberg (509) 480-9112

2022 4CLY. Demo Derby ADDENDUM

Fuel tanks located in from of rear axle can remain in car and be used. (driver AND passenger doors will then have mandatory channel or grader blades ran the length of the car minimum of 6" from each wheel well)

2022 Truck Demolition Derby Rules

Sunday July 3rd, 5:00pm (Chain & Go) \$1000 to Win

Full size pickups only.

4X4 allowed if front drive shaft is removed.

Spread bar must be put in box just behind cab. (minimum of 3" square or round tubing)

(1) One upright bar from floor to roof must be inside of cab as close to driver as possible to protect in case of rollover.

A maximum of <u>14"</u> steel plate must be bolted to the driver's side of vehicle minimum of <u>6"</u> from each wheel well. Passenger side is optional.

Remove existing and replace with boat tank, fuel cell or other approved container. Mounted in box just behind cab next to spread bar.

If dash is removed a spreader bar must be put in place.

All glass and burnable material must be removed. Seats remains.

Battery must be moved inside of cab.

Minimum of $\underline{\mathbf{3}}$ point seatbelt harness must be used.

Minimum of <u>2</u> bars (rebar ok) must be put in both front and back window area to protect driver from large debris items entering.

Doors, hood, & tailgate must be chained (not welded).

Bumpers may be welded to frame.

Stock bumpers must be used for make and model of truck.

NO WELDING ALLOWED ANYWHERE EXCEPT THE WINDOW BARS AND BUMPERS TO FRAME.

No distributor protectors, No engine cradles, No transmission protectors.

Must sign waiver and release form date of race.

Social Security Number required for any payout over \$200.00

Questions? Contact Jeff Gruenberg (509) 480-9112